



**Thread adaptor SRS**

	Thread G	Seal	h		Hex		Version	Order No. SRS	
			mm	in	mm	in			
 <p><b>Version A</b></p>	M10x1	Metal joint Type B	15,5	0.61	17	0.67	A	SRS20-M10x1-B	
	M12x1,5		15	0.59	19	0.75	A	SRS20-M12x1,5-B	
	M14x1,5		15	0.59	19	0.75	A	SRS20-M14x1,5-B	
	M16x1,5		8	0.31	22	0.87	A	SRS20-M16x1,5-B	
	M18x1,5		15	0.59	24	0.94	A	SRS20-M18x1,5-B	
	M22x1,5		10,5	0.41	27	1.06	A	SRS20-M22x1,5-B	
	G <sup>1</sup> / <sub>8</sub>		15,5	0.61	17	0.86	A	SRS20-G <sup>1</sup> / <sub>8</sub> -B	
	G <sup>1</sup> / <sub>4</sub>		15	0.59	19	0.75	A	SRS20-G <sup>1</sup> / <sub>4</sub> -B	
	G <sup>3</sup> / <sub>8</sub>		10,5	0.41	22	0.87	A	SRS20-G <sup>3</sup> / <sub>8</sub> -B	
	G <sup>1</sup> / <sub>2</sub>		10,5	0.41	27	1.06	A	SRS20-G <sup>1</sup> / <sub>2</sub> -B	
	M12x1,5		Elastomeric seal Type C	15	0.59	19	0.75	A	SRS20-M12x1,5-PC
	M14x1,5			15	0.59	19	0.75	A	SRS20-M14x1,5-PC
	M18x1,5			15	0.59	24	0.94	A	SRS20-M18x1,5-PC
	G <sup>1</sup> / <sub>8</sub>			16	0.63	17	0.67	A	SRS20-G <sup>1</sup> / <sub>8</sub> -PC
G <sup>1</sup> / <sub>4</sub>	15	0.59		19	0.75	A	SRS20-G <sup>1</sup> / <sub>4</sub> -PC		
G <sup>3</sup> / <sub>8</sub>	10,5	0.41		22	0.87	A	SRS20-G <sup>3</sup> / <sub>8</sub> -PC		
G <sup>1</sup> / <sub>2</sub>	10,5	0.41		27	1.06	A	SRS20-G <sup>1</sup> / <sub>2</sub> -PC		
R <sup>1</sup> / <sub>4</sub> :K	Taper Type D suitable sealant required	13		0.51	17	0.67	A	SRS20-R <sup>1</sup> / <sub>4</sub> :K-D	
R <sup>3</sup> / <sub>8</sub> :K		13	0.51	19	0.75	A	SRS20-R <sup>3</sup> / <sub>8</sub> :K-D		
R <sup>1</sup> / <sub>2</sub> :K		8	0.31	22	0.87	A	SRS20-R <sup>1</sup> / <sub>2</sub> :K-D		
<sup>1</sup> / <sub>4</sub> NPT		10	0.39	17	0.67	A	SRS20- <sup>1</sup> / <sub>4</sub> NPT-D		
<sup>1</sup> / <sub>2</sub> NPT		8	0.31	22	0.87	A	SRS20- <sup>1</sup> / <sub>2</sub> NPT-D		
 <p><b>Version B</b></p>	<sup>7</sup> / <sub>16</sub> -20UNF	O-Ring Type E	9	0.35	17	0.67	A	SRS20- <sup>7</sup> / <sub>16</sub> UNF-PE	
	<sup>1</sup> / <sub>2</sub> -20UNF		15	0.59	17	0.67	A	SRS20- <sup>1</sup> / <sub>2</sub> UNF-PE	
	<sup>9</sup> / <sub>16</sub> -18UNF		15,5	0.61	19	0.75	A	SRS20- <sup>9</sup> / <sub>16</sub> UNF-PE	
	<sup>7</sup> / <sub>8</sub> -14UNF		11	0.43	27	1.06	A	SRS20- <sup>7</sup> / <sub>8</sub> UNF-PE	
	M14x1,5		14,5	0.57	19	0.75	A	SRS20-M14x1,5-PE	
	M16x1,5		8,5	0.33	22	0.87	A	SRS20-M16x1,5-PE	
	M22x1,5		10	0.39	27	1.06	A	SRS20-M22x1,5-PE	
	M27x2		10	0.39	32	1.26	A	SRS20-M27x2-PE	
	M14x1,5		Metal joint Type B	24	0.94	19	0.75	B	SRS15-M14x1,5-B
	M16x1,5			24	0.94	22	0.87	B	SRS15-M16x1,5-B
	M18x1,5			24	0.94	24	0.94	B	SRS15-M18x1,5-B
M20x1,5	10,5	0.41		27	1.06	B	SRS15-M20x1,5-B		
G <sup>3</sup> / <sub>8</sub>	24	0.94		22	0.87	B	SRS15-G <sup>3</sup> / <sub>8</sub> -B		
G <sup>1</sup> / <sub>2</sub>	10,5	0.41		27	1.06	B	SRS15-G <sup>1</sup> / <sub>2</sub> -B		
M14x1,5	Elastomeric seal Type C	24		0.94	19	0.75	B	SRS15-M14x1,5-PC	
M16x1,5		24		0.94	22	0.87	B	SRS15-M16x1,5-PC	
M18x1,5		24		0.94	24	0.94	B	SRS15-M18x1,5-PC	
G <sup>3</sup> / <sub>8</sub>		24		0.94	22	0.87	B	SRS15-G <sup>3</sup> / <sub>8</sub> -PC	
G <sup>1</sup> / <sub>2</sub>		10,5	0.41	27	1.06	B	SRS15-G <sup>1</sup> / <sub>2</sub> -PC		

TEST