



Test 20 Connection Thread M 16 x 2

Test Hose SMS (for gaseous media Specify Type SGS)

TEST

Max. working pressure 9000 PSI (630 bar) Test hose: Nominal bore 0.08" (2 mm) Minimum bending radius 0.75" (20 mm) Nominal bore 0.16" 4 mm also available Pressure/t° factor: to 0°C 122 % at 30°C 110 % at 50°C 100 % at 80°C 86 % at 100°C 77 % Hose construction: Hose-core and -cover PA Reinforcement: Synthetic fibre Bursting pressure: 27,000 PSI (1900 bar)	Stauff-Test 20/20 STAUFF-TEST 20 Ø5 STAUFF-TEST 20	Stauff-Test 15/20 STAUFF-TEST 20 Ø5 STAUFF-TEST 15	Stauff-Test 10/20 STAUFF-TEST 20 Ø5 STAUFF-TEST 10	Stauff-Test 12/20 (2) STAUFF-TEST 20 Ø5 STAUFF-TEST 12	Stauff-Test 20/N¹/₄ (3) STAUFF-TEST 20 Ø5 1/4" NPT GAUGE ADAPTOR	
	Length L⁽¹⁾					
in	mm	Order No.				
12	305	SMS-20 – 305mm-B	SMS-15/20 – 305mm-B	SMS-10/20 – 305mm-B	SMS-12/20 – 305mm-B	SMS-20/N ¹ / ₄ – 305mm-B
24	610	SMS-20 – 610mm-B	SMS-15/20 – 610mm-B	SMS-10/20 – 610mm-B	SMS-12/20 – 610mm-B	SMS-20/N ¹ / ₄ – 610mm-B
36	915	SMS-20 – 915mm-B	SMS-15/20 – 915mm-B	SMS-10/20 – 915mm-B	SMS-12/20 – 915mm-B	SMS-20/N ¹ / ₄ – 915mm-B
48	1219	SMS-20 – 1219mm-B	SMS-15/20 – 1219mm-B	SMS-10/20 – 1219mm-B	SMS-12/20 – 1219mm-B	SMS-20/N ¹ / ₄ – 1219mm-B
60	1524	SMS-20 – 1524mm-B	SMS-15/20 – 1524mm-B	SMS-10/20 – 1524mm-B	SMS-12/20 – 1524mm-B	SMS-20/N ¹ / ₄ – 1524mm-B
72	1829	SMS-20 – 1829mm-B	SMS-15/20 – 1829mm-B	SMS-10/20 – 1829mm-B	SMS-12/20 – 1829mm-B	SMS-20/N ¹ / ₄ – 1829mm-B
96	2438	SMS-20 – 2438mm-B	SMS-15/20 – 2438mm-B	SMS-10/20 – 2438mm-B	SMS-12/20 – 2438mm-B	SMS-20/N ¹ / ₄ – 2438mm-B
120	3048	SMS-20 – 3048mm-B	SMS-15/20 – 3048mm-B	SMS-10/20 – 3048mm-B	SMS-12/20 – 3048mm-B	SMS-20/N ¹ / ₄ – 3048mm-B
Custom lengths available on request						
(1) Bending protection and other lengths on request			(2) Special thread: buttress thread S 12,65 x 1,5		(3) Gauge adaptor G ¹ / ₄ , G ¹ / ₂ and 1/2 NPT on request	

Transition Adaptor SAD

 M16 x 2 h G	 M16 x 2 h G	G	h in mm	Type	Order No.	
		M16 x 1,5 plug in S 12 ¹⁾	1.53 39	A	NBR (BUNA)	FPM (VITON)
			1.45 37	B	SAD 20/15-P	SAD 20/15-V
			1.53 39	A	SAD 20/10-P	SAD 20/10-V
1) Special thread: buttress thread S 12,65 x 1,5						