



Reducción Schedule 10W  
con soldadura

Acero Inoxidable EN 1.4404/316L  
Acero Inoxidable EN 1.4307/304L

Código		DN	D1 mm	D2 mm	T1 mm	T2 mm	H mm	Peso kg/u.
A-304L	A-316L							
362RS10020015	364RS10020015	3/4" - 1/2"	26,67	21,34	2,11	2,11	38,1	0,10
362RS10025015	364RS10025015	1" - 1/2	33,40	21,34	2,77	2,11	50,8	0,10
362RS10025020	364RS10025020	1" - 3/4"	33,40	26,67	2,77	2,11	50,8	0,13
362RS10032020	364RS10032020	1.1/4" - 3/4"	42,16	26,67	2,77	2,11	50,8	0,15
362RS10032025	364RS10032025	1.1/4" - 1"	42,16	33,40	2,77	2,11	50,8	0,15
362RS10040015	364RS10040015	1.1/2" - 1/2"	48,16	21,34	2,77	2,11	63,5	0,19
362RS10040020	364RS10040020	1.1/2" - 3/4"	48,26	26,67	2,77	2,11	63,5	0,19
362RS10040025	364RS10040025	1.1/2" - 1"	48,26	33,40	2,77	2,77	63,5	0,19
362RS10040032	364RS10040032	1.1/2" - 1.1/4"	48,26	42,16	2,77	2,77	63,5	0,19
362RS10050020	364RS10050020	2" - 3/4"	60,32	26,67	2,77	2,77	76,2	0,29
362RS10050025	364RS10050025	2" - 1"	60,32	33,40	2,77	2,77	76,2	0,29
362RS10050032	364RS10050032	2" - 1.1/4"	60,32	42,16	2,77	2,77	76,2	0,30
362RS10050040	364RS10050040	2" - 1.1/2"	60,32	48,26	2,77	2,77	76,2	0,30
362RS10065040	364RS10065040	2.1/2" - 1.1/2"	73,02	48,26	3,05	2,77	88,9	0,46
362RS10065050	364RS10065050	2.1/2" - 2"	73,02	60,32	3,05	2,77	88,9	0,46
362RS10080040	364RS10080040	3" - 1.1/2"	88,90	48,26	3,05	2,77	88,9	0,57
362RS10080050	364RS10080050	3" - 2"	88,90	60,32	3,05	2,77	88,9	0,57
362RS10080065	364RS10080065	3" - 2.1/2"	88,90	73,02	3,05	2,77	88,9	0,56
362RS10100050	364RS10100050	4" - 2"	114,30	60,32	3,05	2,77	101,6	0,85
362RS10100065	364RS10100065	4" - 2.1/2"	114,30	73,02	3,05	3,05	101,6	0,82
362RS10100080	364RS10100080	4" - 3"	114,30	88,90	3,05	3,05	101,6	0,81
362RS10125080	364RS10125080	5" - 3"	141,30	88,90	3,40	3,05	127,0	1,46
362RS10125100	364RS10125100	5" - 4"	141,30	114,30	3,40	3,05	127,0	1,48
362RS10150080	364RS10150080	6" - 3"	168,27	88,90	3,40	3,05	139,7	1,84
362RS10150100	364RS10150100	6" - 4"	168,27	114,30	3,40	3,05	139,7	1,91
362RS10150125	364RS10150125	6" - 5"	168,27	141,30	3,40	3,40	139,7	1,96
362RS10200100	364RS10200100	8" - 4"	219,08	114,30	3,76	3,40	152,4	2,81
362RS10200125	364RS10200125	8" - 5"	219,08	141,30	3,76	3,40	152,4	3,00
362RS10200150	364RS10200150	8" - 6"	219,08	168,27	3,76	3,40	152,4	2,97
362RS10250150	364RS10250150	10" - 6"	273,05	168,27	4,19	3,40	179	4,14
362RS10250200	364RS10250200	10" - 8"	273,05	219,08	4,19	3,76	179	4,49

