

Gerade Einschraubverschraubungen


Einschraubgewinde: Whitworth-Rohrgewinde - zylindrisch

Straight connectors, male

Stud thread: BSP thread - parallel

Racores para roscar rectos

Rosca de conexión: Rosca Witworth para tubos - cilíndrica



GEV-..SR-WD

Type	Mat.-Nr.	Serie	PN	D1	G	L1	L6	SW1	SW2	g/Stk
● GEV-06SR 1.8 WD	708.1171.100.30	S	630	6	1/8	26.0	12.5	14	17	40
● GEV-06SR 1.4 WD	708.1171.110.30	S	630	6	1/4	28.0	13.0	19	17	54
● GEV-06SR 3.8 WD	708.1171.120.30	S	630	6	3/8	30.0	15.5	22	17	63
● GEV-06SR 1.2 WD	708.1171.125.30	S	630	6	1/2	33.0	18.0	27	17	107
● GEV-08SR 1.8 WD	708.1171.160.30	S	630	8	1/8	30.0	14.0	17	19	42
● GEV-08SR 1.4 WD	708.1171.170.30	S	630	8	1/4	30.0	15.0	19	19	63
● GEV-08SR 3.8 WD	708.1171.180.30	S	630	8	3/8	30.5	15.5	22	19	82
● GEV-08SR 1.2 WD	708.1171.185.30	S	630	8	1/2	33.0	18.0	27	19	108
● GEV-10SR 1.8 WD	708.1171.265.30	S	630	10	1/8	30.5	14.5	19	22	48
● GEV-10SR 1.4 WD	708.1171.270.30	S	630	10	1/4	30.5	14.5	19	22	73
● GEV-10SR 3.8 WD	708.1171.280.30	S	630	10	3/8	31.0	15.0	22	22	89
● GEV-10SR 1.2 WD	708.1171.285.30	S	630	10	1/2	33.5	17.5	27	22	125
● GEV-10SR 3.4 WD	708.1171.290.30	S	630	10	3/4			32	22	166
● GEV-12SR 1.4 WD	708.1171.380.30	S	630	12	1/4	33.0	16.5	22	24	91
● GEV-12SR 3.8 WD	708.1171.390.30	S	630	12	3/8	33.0	17.0	22	24	100
● GEV-12SR 1.2 WD	708.1171.400.30	S	630	12	1/2	33.5	17.5	27	24	135
● GEV-12SR 3.4 WD	708.1171.405.30	S	630	12	3/4	34.0	17.5	32	24	192
● GEV-14SR 1.4 WD	708.1171.500.30	S	630	14	1/4	34.0	16.0	24	27	120
● GEV-14SR 3.8 WD	708.1171.502.30	S	630	14	3/8	37.0	18.5	24	27	130
● GEV-14SR 1.2 WD	708.1171.504.30	S	630	14	1/2	37.0	19.0	27	27	154
● GEV-14SR 3.4 WD	708.1171.506.30	S	630	14	3/4	39.0	21.0	32	27	195
● GEV-14SR 1.1 WD	708.1171.510.30	S	630	14	1	41.0	23.0	41	27	350
● GEV-16SR 3.8 WD	708.1171.564.30	S	400	16	3/8	35.0	18.0	27	30	156
● GEV-16SR 1.2 WD	708.1171.566.30	S	400	16	1/2	37.0	18.5	27	30	161
● GEV-16SR 3.4 WD	708.1171.568.30	S	400	16	3/4	39.0	20.5	32	30	226
● GEV-16SR 1.1 WD	708.1171.570.30	S	400	16	1			41	30	348
● GEV-20SR 1.2 WD	708.1171.706.30	S	400	20	1/2	42.0	20.5	32	36	245
● GEV-20SR 3.4 WD	708.1171.708.30	S	400	20	3/4	42.0	20.5	32	36	277
● GEV-20SR 1.1 WD	708.1171.712.30	S	400	20	1	44.0	22.5	41	36	387
● GEV-20SR 3.2 WD	708.1171.717.30	S	400	20	1 1/2	47.0	25.5	55	36	782

Fortsetzung nächste Seite

Continued on next page

Continuación página próxima



LEHENGOTAK, S. A.

Gerade Einschraubverschraubungen


Einschraubgewinde: Whitworth-Rohrgewinde - zylindrisch

Straight connectors, male

Stud thread: BSP thread - parallel

Racores para roscar rectos

Rosca de conexión: Rosca Witworth para tubos - cilíndrica



GEV-..SR-WD

Type	Mat.-Nr.	Serie	PN	D1	G	L1	L6	SW1	SW2	g/Stk
● GEV-06SR 1.8 WD	708.1171.100.30	S	630	6	1/8	26.0	12.5	14	17	40
● GEV-06SR 1.4 WD	708.1171.110.30	S	630	6	1/4	28.0	13.0	19	17	54
● GEV-06SR 3.8 WD	708.1171.120.30	S	630	6	3/8	30.0	15.5	22	17	63
● GEV-06SR 1.2 WD	708.1171.125.30	S	630	6	1/2	33.0	18.0	27	17	107
● GEV-08SR 1.8 WD	708.1171.160.30	S	630	8	1/8	30.0	14.0	17	19	42
● GEV-08SR 1.4 WD	708.1171.170.30	S	630	8	1/4	30.0	15.0	19	19	63
● GEV-08SR 3.8 WD	708.1171.180.30	S	630	8	3/8	30.5	15.5	22	19	82
● GEV-08SR 1.2 WD	708.1171.185.30	S	630	8	1/2	33.0	18.0	27	19	108
● GEV-10SR 1.8 WD	708.1171.265.30	S	630	10	1/8	30.5	14.5	19	22	48
● GEV-10SR 1.4 WD	708.1171.270.30	S	630	10	1/4	30.5	14.5	19	22	73
● GEV-10SR 3.8 WD	708.1171.280.30	S	630	10	3/8	31.0	15.0	22	22	89
● GEV-10SR 1.2 WD	708.1171.285.30	S	630	10	1/2	33.5	17.5	27	22	125
● GEV-10SR 3.4 WD	708.1171.290.30	S	630	10	3/4			32	22	166
● GEV-12SR 1.4 WD	708.1171.380.30	S	630	12	1/4	33.0	16.5	22	24	91
● GEV-12SR 3.8 WD	708.1171.390.30	S	630	12	3/8	33.0	17.0	22	24	100
● GEV-12SR 1.2 WD	708.1171.400.30	S	630	12	1/2	33.5	17.5	27	24	135
● GEV-12SR 3.4 WD	708.1171.405.30	S	630	12	3/4	34.0	17.5	32	24	192
● GEV-14SR 1.4 WD	708.1171.500.30	S	630	14	1/4	34.0	16.0	24	27	120
● GEV-14SR 3.8 WD	708.1171.502.30	S	630	14	3/8	37.0	18.5	24	27	130
● GEV-14SR 1.2 WD	708.1171.504.30	S	630	14	1/2	37.0	19.0	27	27	154
● GEV-14SR 3.4 WD	708.1171.506.30	S	630	14	3/4	39.0	21.0	32	27	195
● GEV-14SR 1.1 WD	708.1171.510.30	S	630	14	1	41.0	23.0	41	27	350
● GEV-16SR 3.8 WD	708.1171.564.30	S	400	16	3/8	35.0	18.0	27	30	156
● GEV-16SR 1.2 WD	708.1171.566.30	S	400	16	1/2	37.0	18.5	27	30	161
● GEV-16SR 3.4 WD	708.1171.568.30	S	400	16	3/4	39.0	20.5	32	30	226
● GEV-16SR 1.1 WD	708.1171.570.30	S	400	16	1			41	30	348
● GEV-20SR 1.2 WD	708.1171.706.30	S	400	20	1/2	42.0	20.5	32	36	245
● GEV-20SR 3.4 WD	708.1171.708.30	S	400	20	3/4	42.0	20.5	32	36	277
● GEV-20SR 1.1 WD	708.1171.712.30	S	400	20	1	44.0	22.5	41	36	387
● GEV-20SR 3.2 WD	708.1171.717.30	S	400	20	1 1/2	47.0	25.5	55	36	782

Fortsetzung nächste Seite

Continued on next page

Continuación página próxima



LEHENGOTAK, S. A.