

## Gerade Einschraubverschraubungen

Einschraubgewinde: Whitworth-Rohrgewinde - zylindrisch


## Straight connectors, male

Stud thread: BSP thread - parallel

## Racores para roscar rectos

Rosca de conexión: Rosca Whitworth para tubos - cilíndrica

### GEV-..SR



Type	Mat.-Nr.	Serie	PN	D1	G	L1	L6	SW1	SW2	g/Stk
GEV-06SR 1.8	708.1141.100.30	S	630	6	1/8	26.0	12.5	14	17	40
● GEV-06SR 1.4	708.1141.110.30	S	630	6	1/4	28.0	13.0	19	17	54
GEV-06SR 3.8	708.1141.120.30	S	630	6	3/8	30.0	15.5	22	17	63
GEV-06SR 1.2	708.1141.125.30	S	630	6	1/2	33.0	18.0	27	17	107
GEV-06SR 3.4	708.1141.126.30	S	630	6	3/4	35.0	20.0	32	17	152
GEV-08SR 1.8	708.1141.160.30	S	630	8	1/8	30.0	14.0	17	19	
● GEV-08SR 1.4	708.1141.170.30	S	630	8	1/4	30.0	15.0	19	19	63
GEV-08SR 3.8	708.1141.180.30	S	630	8	3/8	30.5	15.5	22	19	82
GEV-08SR 1.2	708.1141.185.30	S	630	8	1/2	33.0	18.0	27	19	108
GEV-10SR 1.8	708.1141.265.30	S	630	10	1/8	30.5	14.0	19	22	
GEV-10SR 1.4	708.1141.270.30	S	630	10	1/4	30.5	14.5	19	22	73
● GEV-10SR 3.8	708.1141.280.30	S	630	10	3/8	31.0	15.0	22	22	89
GEV-10SR 1.2	708.1141.285.30	S	630	10	1/2	33.5	17.5	27	22	125
GEV-10SR 3.4	708.1141.290.30	S	630	10	3/4			32	22	
GEV-12SR 1.4	708.1141.380.30	S	630	12	1/4	33.0	16.5	22	24	91
● GEV-12SR 3.8	708.1141.390.30	S	630	12	3/8	33.0	17.0	22	24	100
GEV-12SR 1.2	708.1141.400.30	S	630	12	1/2	33.5	17.5	27	24	135
GEV-12SR 3.4	708.1141.405.30	S	630	12	3/4	34.0	17.5	32	24	192
GEV-14SR 1.4	708.1141.500.30	S	630	14	1/4	34.0	16.0	24	27	118
GEV-14SR 3.8	708.1141.502.30	S	630	14	3/8	37.0	18.5	24	27	130
● GEV-14SR 1.2	708.1141.504.30	S	630	14	1/2	37.0	19.0	27	27	154
GEV-14SR 3.4	708.1141.506.30	S	630	14	3/4	39.0	21.0	32	27	195
GEV-14SR 1.1	708.1141.510.30	S	630	14	1	41.0	23.0	41	27	350
GEV-16SR 3.8	708.1141.564.30	S	400	16	3/8	35.0	18.0	27	30	156
● GEV-16SR 1.2	708.1141.566.30	S	400	16	1/2	37.0	18.5	27	30	161
GEV-16SR 3.4	708.1141.568.30	S	400	16	3/4	39.0	20.5	32	30	240
GEV-16SR 1.1	708.1141.570.30	S	400	16	1			41	30	348
GEV-20SR 1.2	708.1141.706.30	S	400	20	1/2	42.0	20.5	32	36	245
● GEV-20SR 3.4	708.1141.708.30	S	400	20	3/4	42.0	20.5	32	36	277
GEV-20SR 1.1	708.1141.712.30	S	400	20	1	44.0	22.5	41	36	387
GEV-20SR 5.4	708.1141.715.30	S	400	20	1 1/4	44.0	22.5	50	36	574
GEV-20SR 3.2	708.1141.717.30	S	400	20	1 1/2	47.0	25.5	55	36	778

Fortsetzung nächste Seite

Continued on next page

Continuación página próxima



# LEHENGOMAK, S. A.

## Gerade Einschraubverschraubungen


Einschraubgewinde: Whitworth-Rohrgewinde - zylindrisch

### Straight connectors, male

Stud thread: BSP thread - parallel

### Racores para roscar rectos

Rosca de conexión: Rosca Whitworth para tubos - cilíndrica

**GEV-..SR**


Type	Mat.-Nr.	Serie	PN	D1	G	L1	L6	SW1	SW2	g/Stk
GEV-25SR 1.2	708.1141.800.30	S	400	25	1/2	47.0	23.0	41	46	444
GEV-25SR 3.4	708.1141.805.30	S	400	25	3/4	45.0	23.0	41	46	455
● GEV-25SR 1.1	708.1141.810.30	S	400	25	1	47.0	23.0	41	46	494
GEV-25SR 5.4	708.1141.815.30	S	400	25	1 1/4	47.0	23.0	50	46	674
GEV-25SR 3.2	708.1141.820.30	S	400	25	1 1/2	50.0	26.0	55	46	582
GEV-30SR 3.4	708.1141.895.30	S	400	30	3/4			45	50	
GEV-30SR 1.1	708.1141.900.30	S	400	30	1	50.0	23.5	46	50	580
● GEV-30SR 5.4	708.1141.902.30	S	400	30	1 1/4	50.0	23.5	50	50	670
GEV-30SR 3.2	708.1141.905.30	S	400	30	1 1/2	53.0	26.5	55	50	667
GEV-38SR 5.4	708.1141.954.30	S	315	38	1 1/4	54.0	23.0	55	60	920
● GEV-38SR 3.2	708.1141.953.30	S	315	38	1 1/2	57.0	26.0	55	60	935

Baumaße sind Ungefährmaße bei angezogener Überwurfmutter.

Sizes are approximate dimensions at tightened nuts.

Las medidas son aproximadas con la tuerca de unión apretada.

Abdichtung durch Dichtkante Form B.

Sealing by stud face form B.

Cierre hermético con junta de obturación forma B.



# LEHENGOMAK, S. A.