

Gerade Einschraubverschraubungen

Einschraubgewinde: Metrisches Gewinde - zylindrisch


Straight connectors, male

Stud thread: metric - parallel

Racores para roscar rectos

Rosca de conexión: Rosca métrica - cilíndrica

GEV-..LM-WD



Type	Mat.-Nr.	Serie	PN	D1	M	L1	L6	SW1	SW2	g/Stk
● GEV-06LM 10x1,0 WD	708.1173.180.20	L	315	6	10x1.0	23.0	8.5	14	14	25
● GEV-06LM 12x1,5 WD	708.1173.190.20	L	315	6	12x1.5	24.5	10.0	17	14	28
● GEV-08LM 12x1,5 WD	708.1173.240.20	L	315	8	12x1.5	25.0	10.0	17	17	40
● GEV-08LM 14x1,5 WD	708.1173.245.20	L	315	8	14x1.5	25.0	10.0	19	17	44
● GEV-08LM 18x1,5 WD	708.1173.255.20	L	315	8	18x1.5	27.5	11.5	24	17	72
● GEV-10LM 10x1,0 WD	708.1173.270.20	L	315	10	10x1.0	26.0	11.0	17	19	44
● GEV-10LM 12x1,5 WD	708.1173.275.20	L	315	10	12x1.5	26.0	11.0	17	19	44
● GEV-10LM 14x1,5 WD	708.1173.280.20	L	315	10	14x1.5	26.0	11.0	19	19	50
● GEV-10LM 16x1,5 WD	708.1173.285.20	L	315	10	16x1.5	27.0	12.5	22	19	62
● GEV-10LM 18x1,5 WD	708.1173.288.20	L	315	10	18x1.5	30.0	12.5	24	19	72
● GEV-12LM 14x1,5 WD	708.1173.327.20	L	315	12	14x1.5	30.0	12.5	19	22	62
● GEV-12LM 16x1,5 WD	708.1173.330.20	L	315	12	16x1.5	27.5	12.5	22	22	65
● GEV-12LM 18x1,5 WD	708.1173.333.20	L	315	12	18x1.5	30.0	12.5	24	22	78
● GEV-12LM 22x1,5 WD	708.1173.338.20	L	315	12	22x1.5	32.0	14.0	27	22	110
● GEV-15LM 18x1,5 WD	708.1173.390.20	L	315	15	18x1.5	28.5	13.5	24	27	100
● GEV-15LM 22x1.5 WD	708.1173.395.20	L	315	15	22x1.5	33.0	15.0	27	27	120
● GEV-18LM 22x1,5 WD	708.1173.460.20	L	315	18	22x1.5	31.0	14.5	27	32	137
● GEV-18LM 26x1,5 WD	708.1173.465.20	L	315	18	26x1.5	33.0	14.5	32	32	170
● GEV-22LM 26x1,5 WD	708.1173.535.20	L	160	22	26x1.5	33.0	16.5	32	36	190
● GEV-28LM 33x2,0 WD	708.1173.570.20	L	160	28	33x2.0	34.0	17.5	41	41	265
● GEV-35LM 42x2,0 WD	708.1173.600.20	L	160	35	42x2.0	39.0	17.5	50	50	440
● GEV-42LM 48x2,0 WD	708.1173.992.20	L	160	42	48x2.0	42.0	19.0	55	60	620

Baumaße sind Ungefährmaße bei angezogener Überwurfmutter.

Sizes are approximate dimensions at tightened nut.

Las medidas son aproximadas con la tuerca de unión apretada.

Abdichtung durch Profildichtung FPM

Sealing by captive FPM seal.

Cierre hermético mediante junta con perfil FPM.



LEHENGOMAK, S. A.