

Gerade Einschraubverschraubungen


Einschraubgewinde: Metrisches Gewinde - zylindrisch

Straight connectors, male

Stud thread: metric - parallel

Racores para roscar rectos

Rosca de conexión: Rosca métrica - cilíndrica

GEV-..SM


Type	Mat.-Nr.	Serie	PN	D1	M	L1	L6	SW1	SW2	g/Stk
● GEV-06SM 12x1,5	708.1143.195.30	S	630	6	12x1.5	28.0	13.0	17	17	48
● GEV-06SM 14x1,5	708.1143.198.30	S	630	6	14x1.5	28.0	13.0	19	17	56
● GEV-08SM 14x1,5	708.1143.245.30	S	630	8	14x1.5	30.0	15.0	19	19	64
● GEV-10SM 16x1,5	708.1143.285.30	S	630	10	16x1.5	31.0	15.0	22	22	88
● GEV-12SM 18x1,5	708.1143.333.30	S	630	12	18x1.5	33.0	17.0	24	24	110
● GEV-14SM 20x1,5	708.1143.382.30	S	630	14	20x1.5	37.0	19.0	27	27	150
● GEV-16SM 22x1,5	708.1143.410.30	S	400	16	22x1.5	37.0	18.5	27	30	165
● GEV-20SM 27x2,0	708.1143.506.30	S	400	20	27x2.0	42.0	20.5	32	36	265
● GEV-25SM 33x2,0	708.1143.550.30	S	400	25	33x2.0	47.0	23.0	41	46	490
● GEV-30SM 42x2,0	708.1143.590.30	S	400	30	42x2.0	50.0	23.5	50	50	690
● GEV-38SM 48x2,0	708.1143.954.30	S	315	38	48x2.0	70.0	26.0	55	60	940

Baumaße sind Ungefährmaße bei angezogener Überwurfmutter.

Sizes are approximate dimensions at tightened nuts.

Las medidas son aproximadas con la tuerca de unión apretada.

Abdichtung durch Dichtkante Form B.

Sealing by stud face form B.

Cierre hermético con junta de obturación forma B.



LEHENGOMAK, S. A.