


ACCESORIOS ROSCADOS

Rosca BSP conforme ISO 7/1 (DIN 2999)

 **LEHENGOAK, S. A.**



Tuerca reducción

FIG 241

Acero Inoxidable EN 1.4409/316

Código	D1	D2	L mm	SW mm	Peso kg/u.
504F241008006	1/4"	1/8"	17	14	0,01
504F241010006	3/8"	1/8"	18	14	0,02
504F241010008	3/8"	1/4"	18	19	0,01
504F241015008	1/2"	1/4"	21	22	0,04
504F241015010	1/2"	3/8"	21	22	0,03
504F241020010	3/4"	3/8"	24	30	0,06
504F241020015	3/4"	1/2"	24	30	0,05
504F241025015	1"	1/2"	26	36	0,10
504F241025020	1"	3/4"	26	36	0,08
504F241032015	1.1/4"	1/2"	29	46	0,19
504F241032020	1.1/4"	3/4"	29	46	0,17
504F241032025	1.1/4"	1"	29	46	0,13
504F241040020	1.1/2"	3/4"	31	50	0,31
504F241040025	1.1/2"	1"	31	50	0,27
504F241040032	1.1/2"	1.1/4"	31	50	0,20
504F241050025	2"	1"	35	65	0,35
504F241050032	2"	1.1/4"	35	65	0,36
504F241050040	2"	1.1/2"	35	65	0,30
504F241065040	2.1/2"	1.1/2"	46	80	0,65
504F241065050	2.1/2"	2"	46	80	0,55
504F241080050	3"	2"	48	93	1,03
504F241080065	3"	2.1/2"	48	93	0,84
504F241100050	4"	2"	52	120	1,99
504F241100065	4"	2.1/2"	52	120	1,63
504F241100080	4"	3"	52	120	1,49



LEHENGOAK, S. A.